

水性建筑涂料内墙专用 YP 系列色浆

○产品说明

水性建筑涂料内墙专用 YP 系列色浆专为内墙乳胶漆调色设计，主要应用于家装小批量调色。具有稳定性强、使用便捷、性价比高等特点。

○应用及使用

主要应用于内墙乳胶漆着色，在使用本产品前，建议先做相容性实验，应充分搅拌均匀，避免沉淀而影响添加量；色浆使用后应及时盖好，避免表面受污染或挥发，影响产品品质。

○产品参数

色浆编号	颜料索引号	原色	浅色	耐候性		耐光性		颜料含量 (%)
				原色	浅色	原色	浅色	
YP505 碳黑	P. BK. 7			4-5	4	7-8	7	35
YP505A 碳黑	P. BK. 7			4-5	4	7-8	7	35
YP304 酞菁蓝	P. B. 15:1			5	5	8	8	32
YP304A 酞菁蓝	P. B. 15:1			5	5	8	8	18
YP601 绿	P. G. 7			5	4-5	8	7-8	30
YP601A 绿	P. G. 7			5	4-5	8	7-8	17
YP602 翠绿	调色			5	4-5	8	7-8	35
YP602A 翠绿	调色			5	4-5	8	7-8	35
YP208 金黄	调色			4	3-4	7	6-7	23
YP208A 金黄	调色			4	3-4	7	6-7	20
YP111 大红	P. R. 2			3-4	2-3	7	6	36
YP111A 大红	P. R. 2			3-4	2-3	7	6	21

★耐光性、耐候性、耐化学性参数是来源于颜料结构性能。耐光性 8 级为最好，1 级为最差；耐候性 5 级为最好，1 级为最差。所有数据均由颜料供应商提供，建议作单独测试耐光性等级相对于蓝羊毛标准（1=差，8=没有变化），d=增深。